

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application.

LISTING OF CLAIMS:

1. (currently amended) Removably attachable shielding  
2 to protect vehicle side surfaces and doors to prevent dents and  
scratches imposed by doors of adjacent vehicles, said shielding  
4 comprising:

two shield pads of impact absorbing material,

6 at least one suction cup on each of said shield pads for  
removable attachment of the shield pad on a vehicle,

8 at least one strap secured to a lateral edge portion of  
each of said shield pads to connect them together,

10 an elastic strap having an end thereof secured to an edge  
portion of a first one of the shield pads, and

12 fastener means for detachably securing a second end portion  
of the elastic strap to a second one of the shield pads,

14 whereby the protective shields are removably attachable to  
vehicle sides- side surfaces and doors, and removable therefrom  
16 and rollable together.

2. Canceled

3. Canceled

4. Canceled

5. (original)

Shielding according to Claim 1, wherein:

2                   cooperating male and female snap fastener components  
are mounted, one on an end portion of the elastic strap and  
4                   the other on an edge portion of one of the shield pads for  
securement of the shield pads together when rolled up together.

6. (original)

Shielding according to Claim 1, wherein two spaced-  
2                   apart straps are secured to an edge portion of each of the  
shield pads by riveting.

7. Canceled

8. Canceled

9. Canceled

10. (currently amended) Removably attachable shielding  
2 to protect vehicle side surfaces and doors to prevent dents and  
scratches imposed by doors of adjacent vehicles, said shielding  
4 comprising:

two shield pads of impact absorbing material,

6 at least one suction cup on each of said shield pads  
for removable attachment of the shield pad on a vehicle,

8 at least one strap secured to a lateral edge portion  
of each of said shield pads to connect them together,

10 said shield pads and suction cups are adapted and  
arranged for attachment to an interior surface of a vehicle  
12 windshield to serve as a sunshade,

14 an elastic strap having an end thereof secured to an  
edge portion of a first one of the shield pads, and

16 fastener means for detachably securing a second end  
portion of the elastic strap to a second one of the shield pads,

18 whereby the protective shields are removably attachable  
to vehicle ~~sides~~ side surfaces and doors, and rollable up  
together.

11. (currently amended) Removably attachable

2 shielding to protect vehicle side surfaces and doors to prevent  
dents and scratches imposed by doors of adjacent vehicles, said  
4 shielding comprising:

two shield pads of impact-absorbing material,

6 at least one suction cup on each of said shield pads  
for removable attachment of the shield pad on a vehicle,

8 two spaced-apart straps extending between and secured  
by lateral edge portions of the two shield pads,

10 an elastic strap having an end thereof secured to  
an edge portion of a first one of the shield pads, and

12 fastener means for detachably securing a second end  
portion of the elastic strap to a second one of the shield pads,

14 whereby the protective shields are removably attachable  
to vehicle-sides- side surfaces and doors, and removable therefrom  
16 and rollable together.

12. (original) Shielding according to Claim 11,  
2 wherein two spaced-apart suction cups are provided on each  
of the shield pads for attachment to the vehicle.

13. (original) Shielding according to Claim 11,  
2 wherein:

cooperating male and female snap fastener components are  
4 mounted, one on an end portion of the elastic strap and the  
other on an edge portion of one of the shield pads for  
6 securement of the shield pads together when rolled up  
together.

14. (original) Shielding according to Claim 11, wherein  
2 two spaced-apart straps are secured to an edge portion of  
each of the shield pads by riveting.

15. (Previously presented) Shielding according to  
2 Claim 11, wherein said elastic strap is attached to a central  
edge portion of one of the shield pads and is detachably  
4 securable to a central edge portion of the other shield pad  
by one of (a) snap fasteners, (b) hook and loop fasteners.

16. Canceled

17. Canceled

18. (currently amended) Removably attachable shielding

2 to protect vehicle side surfaces and doors to prevent dents and  
scratches imposed by doors of adjacent vehicles, said shielding  
4 comprising:

two shield pads of impact-absorbing material,

6 at least one suction cup on each of said shield pads  
for removable attachment of the shield pad on a vehicle,

8 two spaced-apart straps extending between and secured  
by lateral edge portions of the two shield pads,

10 said shield pads and suction cups being adapted and  
arranged for attachment to an interior surface of a vehicle  
12 windshield to serve as a sunshade,

14 an elastic strap having an end thereof secured to an  
edge portion of a first one of the shield pads, and

16 fastener means for detachably securing a second end  
portion of the elastic strap to a second one of the shield pads,

18 whereby the protective shields are removably attachable  
to vehicle sides - side surfaces and doors, and rollable up  
together.

19. (currently amended) Removably attachable  
2 shielding to protect vehicle side surfaces and doors to prevent  
4 dents and scratches imposed by doors of adjacent vehicles, said  
shielding comprising:

6 two shield pads of impact-absorbing material,

8 at least one suction cup on each of said shield pads  
for removable attachment of the shield pad on a vehicle,

10 at least one strap secured to a lateral edge portion  
12 of each of said shield pads to connect them together,

14 said shield pads and suction cups are adapted and  
16 arranged for attachment to an interior surface of a vehicle  
18 windshield to serve as a sunshade,

20 an elastic strap having an end thereof secured to an  
22 edge portion of a first one of the shield pads, said elastic  
24 strap being attached to a central edge portion of one of the  
26 shield pads and detachably securable to a central edge portion  
28 of the other shield pad by one of (a) snap fasteners, (b) hook  
30 and loop fasteners, and

(continued)

19. (currently amended - continued)

fastener means for detachably securing a second end  
portion of the elastic strap to a second one of the shield pads,

20 C 6  
22 whereby the protective shields are removably attachable  
to vehicle sides side surfaces and doors, and removable therefrom  
and rollable together.

---

20. Canceled

21. Canceled

22. Canceled

23. Canceled

24. Canceled